



Green Power

- AC/AC efficiency up to 95%, less operation cost and more energy saving.
- Output power factor 1.0, more powerful to connect more critical loads.
- Input PF >0.996 and THDi <5%, less power pollution and lower TCO



Flexible Rear Panel Configuration

- Dry contact and SNMP are optional.
- Selectable output sockets.
- External battery pack port available.
- Programmable power management outlet (optional)



Hot-swappable Battery Design

- External battery pack is optional.
- Easy for online battery replacement.



User-friendly and Easy-shift LCD Display

- The digital display can be easily shifted through LCD setting to suit for vertical/horizontal installation.



GEN-RM-1101XS



GEN-RM-1102XS GEN-RM-1103XS



GEN-RM-1106XS GEN-RM-1110XS



TECHNICAL SPECIFICATIONS

MODEL	GEN-RM-1101XS	GEN-RM-1102XS	GEN-RM-1103XS	GEN-RM-1106XS	GEN-RM-1110XS
Input					
Voltage (Vac)	120-295			80-275	
Frequency (Hz)	40-70 (50/60Hz auto-sensing)				
Power Factor	≥0.99				
THDi	<4% (full linear load)				
Output					
Capacity (VA)	1000	2000	3000	6000	10000
AC/AC Efficiency Max.	92.5%	93.5%	93.8%	95.5%	95.5%
Power Factor	1.0 up to 40°; 0.9 >40°				
Voltage (Vac)	208/220/230/240±1% (selectable on display panel)				
Frequency (Hz)	50/60±0.1 (battery mode)				
THDv	THD <2% (linear load), THD < 3% (nonlinear load)			THD <1% (linear load), THD < 4% (nonlinear load)	
Overload*	PF0.9:101~105% load long run,106~110% load 10 mins, 111~130% load 1 min, 131~150% load 1s, above 150% load 200 ms PF1.0:101~105% 1min,106~120% 5s, over 120% 200 ms			101~105% Long run, 106~130% load for 10mins, 131~150% 30s, over 150% 500ms.	
Transfer Time	0				
Current Crest Ratio	3:1				
Battery(*)					
Voltage (Vdc)	36	48	72	192-240	
UPS Internal Battery (VRLA)	3×7Ah/12V	4×9Ah/12V	6×9Ah/12V	2*8×7Ah/12V	2*8×9Ah/12V
External Battery Module (EBM) Model	B2U-36-01-2B	B2U-48-02-2B	B2U-72-03-2B	B3U-192-20-2C	B3U-192-20-2C
EBM battery (VRLA)	2*3*7AH/12V	2*4*9AH/12V	2*6*9AH/12V	2*8*7AH/12V	2*8*9AH/12V
Charging Current (A).	Default 1A, (2~8A when adding charger module)			Default 1A, 1~8A settable	
Other					
Communication Interface	RS232+EPO (SNMP, USB,RS485+Dry contact are optional in slot)				
Output Outlet	8×IEC320 C13	8×IEC320 C13 + 1×IEC320 C19		Terminal + 2×IEC320 C13	
Display	Blue screen LCD (Software rotate)				
Display Details	AC input & output voltage, frequency, Load level, Battery level, Temperature; AC mode, Battery mode, Bypass mode, and Fault				
Alarm	Low battery, Abnormal AC input, UPS failure, etc.				
Protection	Low battery, overload, short-circuit and over temperature, etc.				
Noise (dB)	< 50			< 55	
Working Temperature*	-5~ 50°C (40~50 °C auto derating)				
Relative Humidity	0 ~ 95%, No condensation				
Altitude (m)	No derate up to 1000m, max 4000m 30% derate.				
Regulatory Approvals	CE, IEC62040-1, IEC62040-2				
UPS (W×D×H)(mm)	438×420×87(2U)	438×570×87(2U)		438×660×174(4U)	
UPS Weight (kg)	14	20	26	55.6	64
External Battery Module (W×D×H) (mm)	438×420×87(2U)	438×570×87 (2U)	438×570×87 (2U)	438×500×130 (3U)(16*7/9AH)	
Battery Cabinet Weight (kg)	20	29	40	45	48

* Specification is subject to change without prior notice.

(*) The backup time can be customized from minutes to hours, using VRLA or Lithium batteries.